

TK-D240/D340

DMR

VHF/UHF DIGITAL TRANSCEIVER

FleetSync[®]
by KENWOOD

Ergonomically styled yet tough enough to comply with both MIL-STD and IP54/55 environmental standards, these portables provide the features and performance needed for a wide range of workplaces – from warehouses and stations to shops and hotels. As well as handling both analog and digital communications, these user-friendly DMR radios can even operate in direct mode, without a repeater. They also offer such KENWOOD added value as Call Interrupt and 1-watt audio output. These truly resourceful team members will enable you to make the most of your legacy analog equipment while also benefitting from digital communications.

Two-slot TDMA

Belonging to the DMR Tier II category, which covers licensed conventional systems, these radios are specified for 2-slot Time Division Multiple Access (TDMA) operation in 12.5 kHz channels. This means they can offer greater spectrum efficiency.

Two-in-One – Digital & Analog

These DMR radios can operate in both digital and FM analog modes, switching automatically as needed. Interoperability with legacy analog radios allows organizations to migrate to full digital at their own pace.

Dual-slot Direct Mode

Up to two simultaneous subscriber calls can be supported in a 12.5 kHz channel, without requiring a base station or repeater, thus doubling channel capacity.

Call Interruption

In an emergency or whenever a user needs to interrupt a call, Call Interruption is available in both direct and repeater modes, while encoding or decoding. There is also a Lone Worker function to protect employees working alone.

Tough All-terrain

These portable radios conform to MIL-STD C/D/E/F/G standards for ruggedness, and are IP54/55 rated for dust & water protection, making them more than capable of withstanding harsh operating conditions.

Longer Battery Life

Battery life is always important for radio users. Both Lithium-ion and Ni-MH rechargeable batteries are available. Regardless of battery type, operating hours are longer in digital mode.

Clear, Powerful Audio

A radio's most important quality is clarity – being able to hear, loud and clear, what the other party is saying. And these portables deliver just that. For a start, there is 1 W of audio output power, while the AMBE+2™ VOCODER technology accurately replicates natural human speech nuances for superior voice quality, even with high levels of ambient noise. Additionally, Voice Announcement can confirm the channel number, so there is no need to look at the display. English is the default language, but Spanish and French are also available*.

*Availability varies depending on the region.

Slim Styling

Compact form with ergonomically stylish design make these radios easy to grip and operate.

Other features

- Max. 32 ch in 2 zones (16 ch per zone) • Wide 70 MHz UHF coverage • Selectable 8- or 16-channel using channel stopper • 5/1 W (VHF), 4/1 W (UHF) output
- Audio output power 1 W @ 12 Ω • Scanning functions
- Password protection (read/overwrite) • Minimum volume setting • Embedded message • Selective call alert LED • Key Lock • Late entry • Analog signalling: QT/DQT, FleetSync, 2-tone (available later)
- Compander per channel • Squelch level

TKR-D710/D810 VHF/UHF DIGITAL REPEATER



KTI-5
INTERFACE BOX

- DMR Tier II Compatible Air Interface • DMR Digital Conventional & FM Analog Conventional modes
- 136-174 MHz, 50-5 W; 450-520 MHz, 40-5 W; 400-470 MHz, 40-5 W • 30 Channel Capacity • 6 Backlit Programmable Function Keys • Two-digit LED Display
- Conventional IP Network* • AIS IP Console Interface*

*Requires Interface Box KTI-5 installed with the IP Network Software.

Note: The TKR-D710/D810 is not compatible with duplex/simplex base operation but only for repeater operation.



OPTIONS

■ **KNB-29N**
Ni-MH BATTERY PACK
(7.4 V/1,500 mAh)



■ **KNB-45L**
Li-ion BATTERY PACK
(7.4 V/2,000 mAh)




■ **KSC-43**
RAPID CHARGER
(for Li-ion KNB-45L & Ni-MH KNB-29N)



■ **KSC-316**
6-POCKET MULTIPLE CHARGER
(6-pocket for Li-ion KNB-45L & Ni-MH KNB-29N)



■ **KSC-356**
6-POCKET MULTIPLE CHARGER
(6-pocket for Li-ion KNB-45L)



■ **KRA-22**
VHF HELICAL ANTENNA
(Low Profile)



■ **KRA-23**
UHF HELICAL ANTENNA
(Low Profile)



■ **KRA-26**
VHF HELICAL ANTENNA
(Standard Length)



■ **KRA-27**
UHF WHIP ANTENNA
(Standard Length)



■ **KRA-41**
VHF STUBBY ANTENNA



■ **KRA-42**
UHF STUBBY ANTENNA



■ **KMC-21**
SPEAKER MICROPHONE
(Compact Size)



■ **KMC-45D**
SPEAKER MICROPHONE



■ **KBH-10**
BELT CLIP



All accessories and options may not be available in all markets. Contact an authorized KENWOOD dealer for details and complete list of all accessories and options.

SPECIFICATIONS

		TK-D240	TK-D340
GENERAL			
Frequency Range		136-174 MHz	400-470 MHz 450-520 MHz
Number of Channels		32 ch / 2 zones (Max. 16 ch/ zone)	
Channel Spacing	Analog	25/12.5 kHz	
	Digital	12.5 kHz	
Operating Voltage		7.5 V DC ± 20 %	
Battery Life (5-5-90, battery saver off)	Analog/Digital	approx. 11.5/13.5 hrs w/KNB-45L	
		approx. 8/10 hrs w/KNB-29N	
Operating Temperature Range		-30 °C to +60 °C (with KNB-45L: -10 °C to +60 °C)	
Frequency Stability		±2.0 ppm	±1.0 ppm
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	w/KNB-45L or KNB-29N	54 x 121.4 x 33.8 mm	
Weight	w/KNB-45L	285 g	
	w/KNB-29N	370 g	

		TK-D240	TK-D340
RECEIVER			
Sensitivity	Digital 1 % BER	0.45 μV	
	Digital 5 % BER	0.3 μV	
	Analog (12 dB SINAD)	0.25 μV	
Adjacent Channel Selectivity	Analog @ 25/12.5 kHz	74/68 dB	
Intermodulation Distortion	Analog	72dB	
Spurious Response	Analog	70 dB	
Audio Distortion		Less than 10 %	
Audio Output		1 W/12 Ω (Internal speaker) 500 mW/8 Ω (External speaker)	
TRANSMITTER			
RF Power Output		5/1 W	4/1 W
Spurious Response		70 dB	
FM Hum & Noise	Analog @ 25/12.5 kHz	45/40 dB	
Audio Distortion		Less than 2 %	
Emission Designator		16K0F3E, 14K0F2D, 14K0F3E, 12K0F2D, 11K0F3E, 7K50F2D, 7K60FXE, 7K60FXD	

Specifications shown are typical.
Analog 25 kHz is not included in the models sold in the USA or US territories.
Analog measurements accord with TIA 603. Digital measurements accord with EN 300 113.
Details and timing of firmware and software updates are subject to change without notice.
Specifications are subject change without notice, due to advancements in technology.
FleetSync® is a registered trademark of JVC KENWOOD Corporation.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
All other trademarks are the property of their respective holders.

ENVIRONMENTAL SPECIFICATIONS

MIL-STD	Method / Procedures				
	810C	810D	810E	810F	810G
Low Pressure	500.1/I	500.2/I, II	500.3/I, II	500.4/I, II	500.5/I, II
High Temperature	501.1/I, II	501.2/I, II	501.3/I, II	501.4/I, II	501.5/I, II
Low Temperature	502.1/I	502.2/I, II	502.3/I, II	502.4/I, II	502.5/I, II
Temperature Shock	503.1/I	503.2/I	503.3/I	503.4/I, II	503.5/I
Solar Radiation	505.1/I	505.2/I	505.3/I	505.4/I	505.5/I
Rain*1	506.1/I, II	506.2/I, II	506.3/I, II	506.4/I, III	506.5/I, III
Humidity	507.1/I, II	507.2/II, III	507.3/II, III	507.4	507.5/II
Salt Fog*1	509.1/I	509.2/I	509.3/I	509.4	509.5
Dust*1	510.1/I	510.2/I	510.3/I	510.4/I, III	510.5/I
Vibration	514.2/VIII, X	514.3/I	514.4/I	514.5/I	514.6/I
Shock	516.2/I, II, V	516.3/I, IV	516.4/I, IV	516.5/I, IV	516.6/I, IV
International Protection Standard					
Dust & Water Protection	IP54/55*1				

*1: The 2-pin connector cover has to be connected to the radio, or the locking bracket has to be attached to the KMC-45D external speaker microphone.

JVCKENWOOD Singapore Pte. Ltd.

1 Ang Mo Kio Street 63 Singapore 569110
www.kenwood.com/sg



ISO9001 Registered
Communications Systems Business Unit
JVC KENWOOD Corporation